

Dimensions suivant la normes UNE-EN 545

Raccordement sur brides PN 10 ou PN 16 , PN 25

Construction : fonte GGG-40 revêtue époxy

Corps (mm)						Poids (kg)		
DN	dn	L	E1	E 2	c	PN 10	PN 16	PN 25
60	40	160	7	7	3/3	5.2	5.2	5.3
60	50					5.7	5.7	5.8
80	40	185				5.7	5.7	6.2
80	50					6.3	6.3	6.8
80	60					7	7	7.6
80	65	190				7.4	7.4	8
100	40	195	7.2	7	7	7	8.1	
100	50				7.5	7.5	8.6	
100	60				7.8	7.8	9	
100	80				8.6	8.6	10	
125	40	185	7.5	7	8.2	8.2	9.8	
125	50				8.8	8.8	10.4	
125	60				9.1	9.1	10.8	
125	80				9.8	9.8	11.9	
125	100				7.2	10.5	10.5	13.2
150	60	190	7.8	7	10.9	10.9	12.6	
150	80			7.2	11.7	11.7	13.8	
150	100			7.5	12.4	12.4	15.1	
150	125			7.8	13.8	13.8	17	
200	80	235	8.4	7	16.4	15.9	19.3	
200	100			7.2	17.2	16.7	20.7	
200	125			7.5	18.7	18.2	22.7	
200	150			7.8	20.5	20	24.5	
250	100	250	9	7.2	21.7	22.1	26.7	
250	125			7.5	23.2	23.6	28.7	
250	150			7.8	25.1	25.5	30.6	
250	200			8.4	28.9	28.8	35.2	
300	100	265	9.6	7.2	27.4	28.6	33.5	
300	125			7.5	28.9	30.1	35.5	
300	150			7.8	30.9	32	37.5	
300	200			8.4	34.7	35.4	42.1	
300	250			9	38.8	40.4	47.7	
350	200	290	10.2	8.4	40.1	43.9	52.8	
350	250			9	44.3	49	58.5	
350	300			9.6	49.5	55	64.8	
400	200	305	10.8	8.4	48.7	52.3	62.9	
400	250			9	53	57.5	68.7	
400	300			9.6	58.3	63.8	75.1	
400	350			10.2	64.5	70.7	84.4	
450	250	600	11.4	9	83.3	86.7	100.4	
450	300			9.6	91	95.2	109.2	
450	350	300	10.8	10.2	69	74.2	90.4	
450	400			10.8	74.4	81.5	99.4	
500	300			9.6	101	115.2	125.3	
500	350	600	12	10.2	109.6	124.7	137	
500	400			10.8	117.8	134.9	148.9	
500	450			11.4	86.4	105.9	118.9	
600	350	600	13.2	10.2	129.5	158.9	166	
600	400			10.8	137.9	169.2	178	
600	450			11.4	145.6	179.4	187.2	
600	500			12	155.7	196.1	203.4	

